


Laser Diode 1550nm 20mW



BLD-1550-14BF Fiber Bragg Grating laser is single frequency laser diode module designed for optical measurement and communication. The laser is packaged in 14-pin standard butterfly package with monitor photodiode and thermo-electric cooler (TEC).

Key Features

- Optical output: 20mW
- Narrow linewidth ($\Delta\nu < 0.1\text{MHz}$)
- Wavelength: 1550nm @ 25°C
- SM or PM Fiber ($\varnothing 0.9\text{mm}$)
- FC-APC connector
- 14-pin butterfly package
- Internal monitor PD and TEC
- Low power consumption

Optical and electrical characteristics: (T = 25°C)

Item	Symbol	Test condition	Min.	Typ.	Max.	Unit
Output Power	P _f			15	20	mW
Forward Voltage	V _F	P _f =15mW			2.5	V
Threshold Current	I _{th}			40	60	mA
Forward Current	I _F	P _f =15mW		200	300	mA
Center Wavelength	λ _c	P _f =15mW	1550+/-0.5			nm
Spectral Width	Δλ	P _f =15mW		100		kHz
Side Mode Suppression Ratio	SMSR	P _f =15mW	40	45		dB
Relative Intensity Noise	RIN	P _f =15mW		-150		dB/Hz
Monitor Current	I _m	P _f =15mW, V _{RD} =5V	40		200	μA
PD Dark Current	I _d	V _{RD} =5V			0.1	μA
Cooler Voltage	V _C	I _F =EOL, TC=70°C			2.7	V
Cooler Current	I _C	I _F =EOL, TC=70°C			1.4	A
Thermal Resistance	R _o	T _{LD} =25°C, B=3900±100K	9.5	10.0	10.5	kΩ
Extinction Ratio	X _P	P _f =15mW	17			dB
Mode Hop Free Range	ΔI			30		mA
Single-Frequency Continuous Tuning Range	Δf		3			GHz
Current Tuning	Δλ/ΔI			0.002		nm/mA
Temperature Tuning	Δλ/ΔT			0.08		nm/°C

Absolute Maximum Ratings

Item	Symbol	Rating	Unit
LD Forward Current	I_f	300	mA
LD Reverse Voltage	V_r	1.8	V
PD Reverse Voltage	V_{RD}	10	V
Operation Case Temperature	T_c	-40 to +70	°C
Storage Temperature	T_{stg}	-40 to +85	°C
Cooler Current	I_c	1.4	A

PACKAGING

No.	FUNCTION	No.	FUNCTION
1	Cooler anode	8	NC
2	Thermistor	9	NC
3	PD anode	10	LD anode
4	PD cathode	11	LD cathode
5	Thermistor	12	NC
6	NC	13	Case
7	NC	14	Cooler anode

