


Laser Diode 980nm 1000mW



BLD-980-14BF Fiber Bragg Grating laser is single frequency laser diode module designed for optical measurement and communication. The laser is packaged in 14-pin standard butterfly package with monitor photodiode and thermo-electric cooler (TEC).

Key Features

- Optical output: 1000mW
- Narrow linewidth
- Pulsed operation
- SM or PM Fiber (ø0.9mm)
- FC-PC connector
- 14-pin butterfly package
- Internal monitor PD and TEC
- Low power consumption

Optical and electrical characteristics: (T = 25°C)

Item	Symbol	Test condition	Min.	Typ.	Max.	Unit
Output Power	P_f			1000		mW
Pulsed Forward Current	I_{FP}	$P_f=1000mW$		1200	1700	mA
Pulse Duration	t_p				100	ns
Duty Cycle	D				0.1	%
Forward Voltage	V_F	$P_f=1000mW$			2.5	V
Threshold Current	I_{th}		20		60	mA
Center Wavelength	λ_c	$P_f=1000mW$	970		985	nm
Spectral Width	$\Delta\lambda$	$P_f=1000mW$			0.1	nm
Monitor Current	I_m	$P_f=1000mW, V_{RD}=5V$	1		1000	μA
PD Dark Current	I_d	$V_{RD}=5V$			0.1	μA
Cooler Voltage	V_C	$I_F=EOL, TC=70^\circ C$			2.7	V
Cooler Current	I_C	$I_F=EOL, TC=70^\circ C$			1.4	A
Thermal Resistance	R_θ	$T_{LD}=25^\circ C, B=3900\pm 100K$	9.5	10.0	10.5	k Ω
Extinction Ratio	X_P	$P_f=1000mW$	17			dB

Absolute Maximum Ratings

Item	Symbol	Rating	Unit
LD Forward Current	I_f	2000	mA
LD Reverse Voltage	V_r	1.8	V
PD Reverse Voltage	V_{RD}	10	V
Operation Case Temperature	T_c	-40 to +70	°C
Storage Temperature	T_{stg}	-40 to +85	°C
Cooler Current	I_c	1.4	A

PACKAGING

No.	FUNCTION	No.	FUNCTION
1	Cooler anode	8	NC
2	Thermistor	9	NC
3	PD anode	10	LD anode
4	PD cathode	11	LD cathode
5	Thermistor	12	NC
6	NC	13	Case
7	NC	14	Cooler cathode

