

## Laser Diode 1350nm 20mW



FPL-1350-14BF is single mode laser diode module designed for optical measurement and communication. The laser is packaged in 14-pin standard butterfly package with monitor photodiode and thermo-electric cooler (TEC). Module is pigtailed with 0,7-1,0 m of single mode polarization maintaining fiber and connectorized by FC/PC connector.

### Key Features

- Optical output: 20mW
- Efficient coupling into single mode fiber
- CW or pulsed operation
- SM or PM Fiber ( $\varnothing 0.9\text{mm}$ )
- FC-PC connector
- 14-pin butterfly package
- Internal monitor PD and TEC
- Low power consumption

### Optical and electrical characteristics: (T = 25°C)

Item	Symbol	Test condition	Min.	Typ.	Max.	Unit
Output Power	$P_f$			20		mW
Forward Voltage	$V_F$	$P_f=20\text{mW}$			2.5	V
Threshold Current	$I_{th}$			30	50	mA
Forward Current	$I_F$	$P_f=20\text{mW}$		150	200	mA
Center Wavelength	$\lambda_c$	$P_f=20\text{mW}$	1340		1350	nm
Spectral Width	$\Delta\lambda$	$P_f=20\text{mW}$		1	3	nm
Monitor Current	$I_m$	$P_f=20\text{mW}, V_{RD}=5\text{V}$	40		500	$\mu\text{A}$
PD Dark Current	$I_d$	$V_{RD}=5\text{V}$			0.1	$\mu\text{A}$
Cooler Voltage	$V_C$	$I_F=EOL, TC=70^\circ\text{C}$			2.7	V
Cooler Current	$I_C$	$I_F=EOL, TC=70^\circ\text{C}$			1.4	A
Thermal Resistance	$R_o$	$T_{LD}=25^\circ\text{C}, B=3900\pm 100\text{K}$	9.5	10.0	10.5	$\text{k}\Omega$
Extinction Ratio	$X_P$	$P_f=20\text{mW}$	17			dB

